



GAS COMPONENTS



ELECTRIC COMPONENTS



WATER TECHNOLOGY



MECHANICAL COMPONENTS



TOOLS

Spare parts suitable for

BAKERS PRIDE

Find the complete and up-to-date range of products in our GEV Webshop



Manufacturer catalogue

The most important spare parts and accessories arranged clearly for every manufacturer

- ✓ Complete product range and all appliance data always up to date in the GEV Webshop
- ✓ Alphabetical Index at the end of the catalogue

GEV Webshop

www.gev-online.co.uk

www.gev-online.com



- 🔍 Add to Favourites
- 🔍 Sign In with email address and usual password
- 🔍 Easy-order – place several items in your basket at the same time
- 🔍 Quick Item search – no login needed




thermostats

control and safety thermostats

EGO

control thermostats

55.34_series



GEV No.	376089	Ref. No.	M1098X
description	thermostat t.max. 370°C temperature range 140-360°C 3-pole probe ø 3.1mm probe L 263mm capillary pipe 1700mm shaft ø 6x4.6mm shaft L 23mm rotation 270°		

CAEM

control thermostats



GEV No.	390790	Ref. No.	182500044
description	thermostat t.max. 300°C temperature range 50-280°C 1-pole 1NO 16A probe ø 3mm probe L 160mm capillary pipe 1450mm capillary pipe isolated 650mm gland nut shaft ø 6x4.6mm shaft L 22mm rotation 270° 250V		

INVENSYS / ROBERTSHAW

control thermostats



GEV No.	376030	Ref. No.	M1032X
description	thermostat t.max. 288°C temperature range 38-288°C 2-pole 2NO 30A probe ø 5mm probe L 295mm capillary pipe 1540mm capillary pipe isolated 650mm gland nut shaft ø 6x4.6mm shaft L 20mm shaft position upper 100-550°F		

GEV No.	376031	Ref. No.	M1031X
description	thermostat t.max. 371°C temperature range 148-371°C 2-pole 2NO 30A probe ø 5mm probe L 285mm capillary pipe 1540mm capillary pipe isolated 650mm gland nut shaft ø 6x4.6mm shaft L 20mm shaft position upper probe material zinc-plated 300-700°F		

switches and momentary switches

rocker/momentary rocker switches

30x22mm



GEV No.	347662	Ref. No.	167600000
description	momentary rocker switch mounting measurements 30x22mm black 2CO 250V 16A steam connection male faston 6.3mm ambient temperature max. 100/55°C protection IP40		

microswitches

pin-plunger actuated

M10



GEV No.	345032	Ref. No.	151600020
description	microswitch with plunger thread M10x1 thread L 12mm 250V 16A 1CO connection male faston 6.3mm stroke 7mm mounting distance 22mm L 28mm ambient temperature max. 125°C type SP9603 actuating force: 180g		



solenoid valves

solenoid valves (water)

RPE

solenoid valves with reducers

single



1

GEV No.	370692	Ref. No.	120800009
description	solenoid valve single straight 220-240VAC inlet 3/4" outlet 11.5mm input 10-12l/min output 0.32-0.42l/min t.max. 60°C duty cycle 100% RPE plastic flow regulating valve outlet green flow regulating valve inlet white 2-ways medium temp max. 25°C		

fans

hot air motors



1

GEV No.	601799	Ref. No.	391500007 391500015
description	fan wheel D1 ø 197mm H1 43mm blades 45 D2 ø 8mm D3 ø 8mm H2 25mm		

ignition parts

pilot burners

ROBERTSHAW

pilot burners

11EA series



1

GEV No.	107411	Ref. No.	M1054X M1055X
description	pilot burner ROBERTSHAW type 11EA 1 flame LPG code 10 for pipe ø 3/16" - 1/4" CCT		



1

GEV No.	107412	Ref. No.	M1062X
description	pilot burner ROBERTSHAW type 11EA 1 flame natural gas for pipe ø 3/16" - 1/4" CCT		

thermocouples

thermocouple sets universal



1

GEV No.	102283	Ref. No.	M1296A M1296X
description	thermocouple set ROBERTSHAW 5-piece L 72" - 1825mm		

equipment-specific units

for pizza ovens

firebricks



1

GEV No.	850125	Ref. No.	T1192X
description	firebrick L 640mm W 528mm H 27mm		

C

control thermostats 3

F

fans 4

H

hot air motors 4

M

microswitches 3

P

pilot burners 4

R

rocker/momentary rocker switches 3

S

solenoid valves 4

switches and momentary switches 3

T

thermocouples 4

thermostats 3